



## OR-E800FB

## 新型全封闭式扫地机 New enclosed sweeper

OR-E800FB采用封闭式驾驶室,适合在寒冷、恶劣的环境下使用。 颜色可定做/标配色:白色 〇

OR-E800FB is featured with the enclosed cab, suitable for cold and harsh environment.

Color can be customized /Making color : White O

## ◀性能特性

- · 采用国内首创先进三轮清扫车超大过滤系统, 过滤面积更大, 吸尘能力更强。
- ·水箱容量为100L,是三轮电动地车中最大的水箱容量。
- · 采用全封闭驾驶室,避免天气、噪音等恶劣条件对清扫工作的影响。双开门,夏天门可拆卸。
- · 采用48V免维护蓄电池为动力, 节能环保, 连续使用时间更长,可选配锂电池。
- · 地机线束符合TS16949标准, 供电可靠, 核心连接器全部阻燃防水。
- · 地系统的核心电机 (主刷电机)采用自主研发的稀土电机。

(具有寿命长、性能稳定、调速精度高、调速比大、输出特性硬、运转平稳的优点。)



## CHARACTERISTICS:

- · Featured with first national advanced extra-large filtration system for three-wheel sweeper, offering larger filtration area, and stronger vacuuming ability.
- · Water tank capacity of 100L, largest of its kind in three-wheel electric sweeper.
- · Designed with fully enclosed cab, avoiding affecting on the cleaning due to the harsh conditions of weather, noise, etc. The double door design is convenient for disassembly in summer.
- · Featured with 48V maintenance-free battery, energy saving and environmentally friendly, longer continuous use, lithium battery optional.
- · Sweeper wiring harness conforms to TS16949 Standard with reliable power supply, all key connectors are retardant and waterproof.
- · Core motor of sweeping system: main brush motor. Featured with self-developed rare earth motor (advantages: long life, stable performance, high speed adjustment precision, large speed ratio, hard output characteristics, and smooth running.)

序号 S/N	项目名称/Item NO.	单位/Unit	参数/Speicification
1	清扫宽度 Sweeping width	mm	≥1900
2	工作效率 Cleaning efficiency	m²/h	>13000
3	爬坡能力 Max gradeability	%	25
4	主刷长度 Main brush's length	mm	800
5	边刷直径 Side brush's diameter	mm	500
6	动力源 Power supply	V	48
7	工作时间 Working time	h	6~8
8	水箱容量 Water tank capacity	L	100
9	尘箱容量 Dustbin capacity	L	180
10	驱动功率 Driving power	W	1800/2500
11	作业功率(电机)主刷+风机+边刷+振尘 Working power (motor) Main brush+fan+side brush+vibration	W	800+700+80×4+50
12	作业功率(电机)Working speed	km/h	7
13	行驶速度 Driving speed	km/h	9.8
14	过滤面积 Filtering area	m²	8
15	转弯半径 Turning radius	mm	1200
16	尺寸 Dimensions(L*W*H)	mm	2100*1900*2040
17	轮胎直径 Wheel diameter	mm	400
18	净重 Net weight	kg	900

